



# TORQU3® STREET COMPETITION API 5W-30 SP/C3 FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Years of research and development on and off the racetrack in close technical collaboration with our technological partners in USA has culminated in the design of this vastly superior ESTER infused fully synthetic. This specific formulation has been purpose built for high torque, turbocharged and/or modified street vehicles. This TORQU3® proprietary formulation brings forth a new dimension in wear protection, engine cleanliness, increased responsiveness, better fuel economy and keeps engines running significantly cooler. Overall leading to an improved drive experience, quicker acceleration and longer engine life. Keeping your vehicle running like new, all the while being a pleasure to drive.

## PERFORMANCE BENEFITS

### SUPERIOR ESTER FORTIFIED FULLY SYNTHETIC FORMULA

- Built from selected fully synthetics & ESTERS purely for performance & quality. Unmatched thermal & shear stability to withstand high oxidative stress & shearing leading to a longer drain interval. Excellent general lubrication.

### ADVANCED ADDITIVE PACKAGE SP

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers. Meets resource conserving ILSAC GF-6A combining increased fuel efficiency and better emissions control.

### LOW VISCOSITY LOW FRICTION

- Increased fuel efficiency, excellent throttle response.

### PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

### MEETS SPECIFICATIONS & APPROVALS

- API SP - ACEA C3 - Porsche C30
- BMW Longlife 04 - VW 504 00 / 507 00
- MB-Approval 229.31 / 229.51 / 229.52
- OV 040 1547 - D30 / G 30 - FIAT 9.55535-S3

### RECOMMENDATIONS

#### SAE 5W30 API SP

- For gasoline engines requiring SAE 5W30 viscosity and API SP performance grade. Can be safely used in vehicles requiring SAE 10W30 viscosities. Backward compatible, meets API SP and supersedes previous categories.

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

## TORQU3® STREET COMPETITION 5W-30 SP/C3 FULLY SYNTHETIC

SAE Viscosity Grade		5W-30
Kinematic viscosity at 40°C (cSt)	ASTM D445	63.85
Kinematic viscosity at 100°C (cSt)	ASTM D445	11.54
Density at 15°C	ASTM D4052	0.8535
Flash point, °C	ASTM D92	234
Pour point, °C	ASTM D97	-50
Viscosity Index	ASTM D2270	178

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

