



# TORQU3® STREET COMPETITION API 5W-50 SP FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Years of research and development on and off the racetrack in close technical collaboration with our technological partners in USA has culminated in the design of this vastly superior ESTER infused fully synthetic. This specific formulation has been purpose built for high torque, turbocharged and/or modified STREET VEHICLES. This TORQU3® proprietary formulation brings forth a new dimension in wear protection, engine cleanliness, increased responsiveness, better fuel economy and keeps engines running significantly cooler. Overall leading to an improved drive experience, quicker acceleration and longer engine life. Keeping your vehicle running like new, all the while being a pleasure to drive.

## PERFORMANCE BENEFITS

### SUPERIOR ESTER FORTIFIED FULLY SYNTHETIC FORMULA

- Built from selected fully synthetics & esters purely for performance & quality. Unmatched thermal & shear stability to withstand high oxidative stress & shearing leading to a longer drain interval. Excellent general lubrication.

### ADVANCED ADDITIVE PACKAGE SP

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers. Combining good fuel efficiency and better emissions control.

### HIGH VISCOSITY

- Fuel efficient, good throttle response.

### PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

### MEETS SPECIFICATIONS & APPROVALS

- API SP
- ACEA A3/B4
- MB-Approval 229.3
- API SN PLUS
- FIAT 9.55535-M2

## RECOMMENDATIONS

### SAE 5W50 API SP

- For gasoline engines specifically requiring SAE 5W50 viscosity and API SP performance grade. Can be safely used in vehicles requiring SAE 10W50 or SAE 15W50 viscosities. Backward compatible, meets API SP and supersedes previous categories.

### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

## TORQU3® STREET COMPETITION 5W-50 SP FULLY SYNTHETIC

SAE Viscosity Grade		5W-50
Kinematic viscosity at 40°C (cSt)	ASTM D445	110.51
Kinematic viscosity at 100°C (cSt)	ASTM D445	18.903
Density at 15°C	ASTM D4052	0.85
Flash point, °C	ASTM D92	225
Pour point, °C	ASTM D97	-51
Viscosity Index	ASTM D2270	192.31

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.