



TORQU3 PRESTIGE PRO API OW-20 SP/C5 FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Developed with the discerning driver in mind, we working in close collaboration with our technological partners in USA have crafted this superior ESTER fortified fully synthetic. This proprietary formulation brings forth a new dimension in wear protection, engine cleanliness, increased responsiveness, better fuel economy and a comparatively lower running temperature. Overall leading to an improved drive experience, quicker acceleration and longer engine life. Keeping your vehicle running like new, all the while being a pleasure to drive.

PERFORMANCE BENEFITS

SUPERIOR FULLY SYNTHETIC FORMULA

- Built from selected fully synthetics for performance & quality. Enhanced thermal stability to withstand high oxidative stress leading to a longer drain interval. Excellent general lubrication.

ADVANCED ADDITIVE PACKAGE SP

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers. Meets resource conserving ILSAC GF-6A combining increased fuel efficiency and better emissions control.

VERY LOW VISCOSITY LOW FRICTION

- Increased fuel efficiency, excellent throttle response.

PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

MEETS SPECIFICATIONS & APPROVALS

- API SP
- ACEA C5
- API SN PLUS
- ILSAC GF-6A
- FORD WSS-M2C962-A1
- Chrysler MS-6395
- FIAT 9.55535-CR1

RECOMMENDATIONS

SAE OW20 API SP

- Specifically for gasoline engines requiring SAE OW20 viscosity and API SP performance grade. Can be safely used in vehicles requiring SAE 5W20 viscosities. Backward compatible, meets API SP and supersedes previous categories.

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3® PRESTIGE PRO OW-20 SP/C5 FULLY SYNTHETIC

SAE Viscosity Grade		OW-20
Kinematic viscosity at 40°C (cSt)	ASTM D445	42.1
Kinematic viscosity at 100°C (cSt)	ASTM D445	8
Density at 15°C	ASTM D4052	0.836
Flash point, °C	ASTM D92	222
Pour point, °C	ASTM D97	-52
Viscosity Index	ASTM D2270	173

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

