



TORQU3® 4T PRESTIGE ENDURO PRO API 15W-50 SP JASO MA 2 FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Developed with the discerning rider in mind, this advanced ESTER-fortified semi-synthetic 4T motorcycle oil has been meticulously engineered in close collaboration with our technological partners in the USA. Formulated using our proprietary blend, it delivers exceptional wear protection, superior engine cleanliness, enhanced throttle responsiveness, and improved fuel efficiency—all while maintaining a cooler operating temperature. The result is a noticeably smoother ride, quicker acceleration, and prolonged engine life. Keep your motorcycle performing at its peak—feeling fresh, powerful, and effortless, ride after ride.

PERFORMANCE BENEFITS

SUPERIOR FULLY SYNTHETIC FORMULA

- Built from selected fully synthetics for performance & quality. Enhanced thermal stability to withstand high oxidative stress leading to a longer drain interval. Excellent general lubrication.

ADVANCED ADDITIVE PACKAGE SP JASO MA 2

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers. Combining good fuel efficiency and better emissions control. While the JASO MA2 specification is recommended for motorcycles with catalytic converters.

HIGH VISCOSITY

- Unsurpassed evaporation control minimizing or eliminating the need for top ups, while giving decent throttle responds. The thick lubricant adds an extra layer of protection even under severe conditions.

PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

MEETS SPECIFICATIONS & APPROVALS

- API SP
- JASO MA 2

RECOMMENDATIONS

SP JASO MA 2

- For 4 stroke motorcycle engines. Indicated where service category SP JASO MA2 is required. Backward compatible, meets API SP JASO MA2 and all previous categories.

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3® 4T PRESTIGE ENDURO PRO 15W-50 SP JASO MA 2 FULLY SYNTHETIC

SAE Viscosity Grade		15W-50
Kinematic viscosity at 40°C (cSt)	ASTM D445	86.3
Kinematic viscosity at 100°C (cSt)	ASTM D445	13.4
Density at 15°C	ASTM D4052	0.8636
Flash point, °C	ASTM D92	205
Pour point, °C	ASTM D97	-40
Viscosity Index	ASTM D2270	159

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

