



# TORQU3® 4T STREET COMPETITION API 10W-50 SP JASO MA 2 FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Years of research and development both on and off the racetrack, in close technical collaboration with our technological partners in the USA, has culminated in the creation of this vastly superior ESTER-infused fully synthetic 4T motorcycle oil. This exclusive formulation is purpose-built for high-performance, high-revving, and modified motorcycles—including those equipped with wet clutches and advanced engine tuning. TORQU3®'s proprietary blend delivers outstanding wear protection, superior clutch performance, enhanced throttle response, improved fuel efficiency, and cooler engine operation. The result is a smoother, faster, and longer-lasting ride, keeping your motorcycle performing like new and making every ride a true pleasure.

## PERFORMANCE BENEFITS

### SUPERIOR ESTER FORTIFIED FULLY SYNTHETIC FORMULA

- Built from selected fully synthetics & esters purely for performance & quality. Unmatched thermal & shear stability to withstand high oxidative stress & shearing leading to a longer drain interval. Excellent general lubrication.

### ADVANCED ADDITIVE PACKAGE SP JASO MA 2

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers. Combining good fuel efficiency and better emissions control. While the JASO MA2 specification is recommended for motorcycles with catalytic converters.

### HIGH VISCOSITY

- Fuel efficient, good throttle response.

### PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

### MEETS SPECIFICATIONS & APPROVALS

- API SP
- JASO MA 2

### RECOMMENDATIONS

#### SP JASO MA 2

- For 4 storke motorcycle engines. Indicated where service category SP JASO MA2 is required. Backward compatible, meets API SP JASO MA2 and all previous categories.

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

## TORQU3® 4T STREET COMPETITION 10W-50 SP JASO MA 2 FULLY SYNTHETIC

SAE Viscosity Grade	Method	10W-50
Kinematic viscosity at 40°C (cSt)	ASTM D445	110
Kinematic viscosity at 100°C (cSt)	ASTM D445	17
Density at 15°C	ASTM D4052	0.85
Flash point, °C	ASTM D92	212
Pour point, °C	ASTM D97	-36
Viscosity Index	ASTM D2270	166

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

