



TORQU3® GL5 85W140 FULLY SYNTHETIC AXLE OIL FOR EXTREME PERFORMANCE AND PROTECTION

(Premium Quality, Multigrade, High Performance Engine Oils)

TORQU3® GL5 85W140 is a premium, fully synthetic axle oil designed to deliver exceptional performance and durability in the most demanding drivetrain applications. Formulated with advanced synthetic base oils and a high-performance additive package, it provides superior lubrication, thermal stability, and wear protection, ensuring optimal performance under extreme operating conditions.

PERFORMANCE BENEFITS

ADVANCED FULLY SYNTHETIC FORMULATION:

- Exceptional oxidation stability for extended oil life and reduced maintenance intervals.
- Superior thermal resistance, maintaining consistent performance in high-temperature environments.
- Excellent low-temperature fluidity for reliable start-up and operation in cold climates.

HIGH-PERFORMANCE GL5 ADDITIVE PACKAGE:

- Extreme pressure (EP) protection to safeguard gears under heavy loads and shock conditions.
- Advanced anti-wear properties to minimize surface fatigue and extend component lifespan.
- Robust rust and corrosion inhibitors to protect metal surfaces from degradation.
- Superior foam control technology to prevent air entrainment and ensure efficient lubrication.
- Seal-compatible formulation to minimize swelling and leakage, enhancing system durability.

85W140 VISCOSITY GRADE:

- Ideal for high-stress, high-load applications, providing exceptional film strength and wear protection.
- Excellent thermal conductivity for efficient heat dissipation, reducing the risk of thermal breakdown under severe operating conditions.

MEETS SPECIFICATIONS & APPROVALS

- API GL-5
- Ford WSS-M2C940-A

RECOMMENDATIONS

API GL5 CERTIFIED:

- Suitable for high-speed, high-torque, and heavy-load applications in both commercial and performance vehicles. Recommended for use in hypoid gears, spiral-bevel gears, and differentials.
- Ideal for off-road vehicles, heavy-duty trucks, and high-performance automotive applications.

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3® GL5 85W140 FULLY SYNTHETIC

SAE Viscosity Grade	Method	85W-140
Kinematic viscosity at 100°C (cSt)	ASTM D445	26
Density at 15°C	ASTM D1298	0.91
Flash point, °C	ASTM D92	204
Pour point, °C	ASTM D97	-12
Viscosity Index	ASTM D2270	97

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.