



TORQU3® 10W30 SN PLUS/CF ECO SYNTHETIC BLEND

(Premium Quality, Multigrade, High Performance Engine Oils)

Developed using cutting edge technology from USA, a premium blend using high end synthetic and selected mineral base stocks together with the best top-tier additives available today TORQU3® 10W30 SN PLUS/CF ECO SYNTHETIC BLEND has developed a medium lower viscosity lubricant that gives excellent throttle response, good fuel efficiency and excellent cleaning performance that keeps your vehicle running like new day after day. While the advanced formulation helps rejuvenate tired engines.

PERFORMANCE BENEFITS

ADVANTAGES & POTENTIAL BENEFITS

- High percentage of fully synthetic base stocks leads to advanced thermal stability to withstand high oxidative stress leading to a longer drain interval. Excellent general lubrication.

ADVANCED ADDITIVE PACKAGE SN PLUS

- SN Plus additive package has better seal compatibility compared to any other previous package. Latest standard with better high temperature deposit protection & sludge control compared to previous packages. Cleaning of carbon deposits left by inferior oils. Optimized timing chain protection and prevention of low speed pre-ignition (LSPI) in gasoline direct injection engines (GDI).

ADVANCED ADDITIVE PACKAGE CF

- Excellent soot & oil thickening control. High anti-foaming characteristics. Reduced valve train wear. Excellent piston deposit control. Enhanced copper corrosion control. Good elastomer compatibility. Reduced oil consumption. Reduced ring & liner wear. Good low temperature pumpability.

PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

MEDIUM LOW VISCOSITY LOW FRICTION

- Increased fuel efficiency over higher viscosity oils, excellent throttle response.

MEETS SPECIFICATIONS & APPROVALS

- API SN PLUS - API SN - ILSAC GF-5

RECOMMENDATIONS

API SN PLUS/CF

- Optimized for gasoline. Recommended where SAE 10W30 and API SN Plus is required. Meets API SN PLUS/CF and supersedes previous categories.

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3® 10W30 SN PLUS/CF ECO SYNTHETIC BLEND

SAE Viscosity Grade	Method	10W-30
Kinematic viscosity at 40°C (cSt)	ASTM D445	66.4
Kinematic viscosity at 100°C (cSt)	ASTM D445	10.5
Density at 15°C	ASTM D4052	0.8665
Flash point, °C	ASTM D92	220
Pour point, °C	ASTM D97	-33
Viscosity Index	ASTM D2270	145

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.