



## TORQU3® CIRCULATING AND BEARING OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Circulating oils for industrial equipment exposed to dynamic water flow. The rapid water separation results in long term reliable operation. They provide long-lasting protection against corrosion and owing to their good oxidation and thermal stability they prevent deposit formation and clogging of filters. Their enhanced antiwear properties extend equipment lifetime. Particularly recommended for Morgoil and similar bearing systems.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO 12925-1 CKB, ISO-L-CKB, DIN 51517-2 (CL), Morgoil Lubricant Spec. Rev. 1.1, SMS SIEMAG-Morgoil Lubricant Spec. SN 180 Part 3, SEB 181225 (CL)

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

**TORQU3**  
LUBRICANTS

### TORQU3® CIRCULATING AND BEARING OILS

Product	100 M	150 M	220 M	320 M	460 M
Kinematic viscosity at 40°C mm <sup>2</sup> /s	100	150	218	310	454
Pour point°C	-12	-12	-12	-12	-9
Flash point (Cleveland)°C	250	250	250	260	275
Density at 15°C g/cm <sup>3</sup>	0.888	0.89	0.892	0.899	0.902

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.