



TORQU3® GAS ENGINE OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Premium quality low ash gas engine oil used for the most advanced, high performance turbocharged stationary gas engines. Especially recommended for natural gas-, methane-, biogas- and LPG-fuelled engines with catalytic converter. Provides long oil change interval. Meets the requirements of the following OEMs: Caterpillar, Waukesha, Deutz, Jenbacher, Wärtsilä, Perkins, Cummins.

PERFORMANCE BENEFITS

PERFORMANCE LEVELS, APPROVALS:

- GE Jenbacher: Series 2, 3, 4 (A, B & D), 6 (C & E) Fuel Class A, B, C, Wärtsilä: 34SG, 32DF, 5ODF, 25SG, 28SG, 175SG, 22OSG (natural gas)

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3
LUBRICANTS

TORQU3® GAS ENGINE OILS

Product	GMO Longlife 40
Kinematic viscosity at 40°C mm ² /s	14.5
Pour point°C	118.5
Flash point (Cleveland)°C	-30
Density at 15°C g/cm ³	0.871

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.