



## TORQU3® HYDRAULIC OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Hydraulic oils for use in hydrostatic transmission systems under normal thermal and mechanical load. They provide good oxidation stability and wear protection, reduce deposit formation and protect hydraulic systems against rust and corrosion. Applicable for machine-tools, industrial, agricultural and off-highway equipment and vehicles.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO 11158 HM, ISO-L-HM, DIN 51524-2 (HLP),  
Cincinnati Lamb P-68, Cincinnati Lamb P-69,  
Cincinnati Lamb P-70, AFNOR NF-E-48603 (HM)

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

**TORQU3**  
LUBRICANTS

### TORQU3® HYDRAULIC OILS

| Product  | Hydro HM 22 | Hydro HM 32 | Hydro HM 46 | Hydro HM 68 | Hydro HM 100 |
|--|-------------|-------------|-------------|-------------|--------------|
| Kinematic viscosity at 40°C mm <sup>2</sup> /s | 23.3        | 32.5        | 44.5        | 66.5        | 100          |
| Pour point°C                                   | -45         | -27         | -30         | -27         | -18          |
| Flash point (Cleveland)°C                      | 190         | 210         | 225         | 240         | 260          |
| Density at 15°C g/cm <sup>3</sup>              | 0.875       | 0.87        | 0.875       | 0.885       | 0.888        |
|  |             |             |             |             |              |
|  |             |             |             |             |              |

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.