



## TORQU3® HYDRO HL HYDRAULIC OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Working fluids for hydraulic power transmission systems operating under low system pressure and equipped mainly with piston pumps. They have excellent thermal and oxidation stability. Owing to their good water separation and air release ability they provide long lasting, reliable operation and long term rust and corrosion protection.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO 11158 HL, ISO-L-HL, DIN 51524-1 (HL),  
DIN 51517-2 (CL)

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

**TORQU3**  
LUBRICANTS

### TORQU3® HYDRO HL HYDRAULIC OILS

Product	Hydro HVLP 32	Hydro HVLP 46	Hydro HVLP 68
Kinematic viscosity at 40°C mm <sup>2</sup> /s	32.6	46.4	69.4
Pour point°C	-21	-24	-21
Flash point (Cleveland)°C	215	220	230
Density at 15°C g/cm <sup>3</sup>	0.87	0.875	0.885

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.