



TORQU3® MULTIGRADE HYDRAULIC OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Multigrade, high performance hydraulic oils. They provide good shear stability and unique temperature- viscosity characteristics to enable reliable operation at both low and high temperatures. Applicable for outdoor hydraulic equipment operated under high thermal and mechanical loads and for industrial and automotive hydraulic systems operated under wide temperature ranges where they ensure superior wear protection and good filterability along with long equipment lifetime.

PERFORMANCE BENEFITS

PERFORMANCE LEVELS, APPROVALS:

- ZETOR, ISO 11158 HV, ISO-L-HV, DIN 51524-3 (HVLP), Parker Hannifin (Denison) HF-O/HF-1/HF-2, SAE MS1004 Type HV, AFNOR NF-E-48603 (HVLP)

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3
LUBRICANTS

TORQU3® MULTIGRADE HYDRAULIC OILS

Product	Hydro HV 15	Hydro HV 22	Hydro HV 32	Hydro HV 46	Hydro HV 68	Hydro HV 100
Kinematic viscosity at 40°C mm ² /s	15.5	21.6	32.7	45.1	68.4	103
Pour point°C	-54	-48	-42	-42	-33	-33
Flash point (Cleveland)°C	170	185	205	220	230	230
Density at 15°C g/cm ³	0.867	0.87	0.86	0.865	0.88	0.884

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.