



TORQU3® PREMIUM GAS TURBINE OIL

(Premium Quality, Multigrade, High Performance Engine Oils)

Specifically designed for high reliability, long service cycle turbines and similar industrial applications. It is made from a carefully selected combination of high quality Group II and Group III base oils and antioxidant, corrosion inhibitors and antiwear additives allowing long oil life and outstanding performance. Exceptionally resistant to local high temperatures, oxidation processes, resulting in high performance for a very long time, designed especially for the most severe stationary gas turbine applications where extreme long service intervals are provided.

PERFORMANCE BENEFITS

PERFORMANCE LEVELS, APPROVALS:

- ISO 8068, DIN 51515-1 L-TD, DIN 51515-2 L-TG, Siemens TLV 901304, Siemens TLV 901305, Solar Turbines ES 9-224 Class II, SKODA POWER, ASTM D 4304 Type I

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3
LUBRICANTS

TORQU3® PREMIUM GAS TURBINE OIL

| Product | Turbine HT 32 |
|--|---------------|
| Kinematic viscosity at 40°C mm ² /s | 32 |
| Pour point°C | -30 |
| Flash point (Cleveland)°C | 210 |
| Density at 15°C g/cm ³ | 0.855 |
| | |
| | |

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.