



## TORQU3® PREMIUM HYDRAULIC OIL

(Premium Quality, Multigrade, High Performance Engine Oils)

Hydraulic oil with high performance level and excellent anti-ageing properties, having a controlled ISO cleanliness (max. 18/16/13). Provides increased drain interval with outstanding reliability. Meets the requirements of hydraulic systems operating under severe, heavy-duty conditions. Applicable in hydraulic systems of machine-tools, industrial equipment, vehicles, agricultural and off-highway equipment.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO 11158 HM, ISO-L-HM, DIN 51524-2 (HLP), SAE MS1004 Type HM, SEB 181222 (HLP), AFNOR NFE-48603 (HM)

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3  
LUBRICANTS

### TORQU3® PREMIUM HYDRAULIC OIL

Product	Hydro HME 100 18/16/13
Kinematic viscosity at 40°C mm <sup>2</sup> /s	101.5
Pour point°C	-18
Flash point (Cleveland)°C	245
Density at 15°C g/cm <sup>3</sup>	0.884

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.