



TORQU3® PREMIUM HYDRAULIC OIL

(Premium Quality, Multigrade, High Performance Engine Oils)

Hydraulic oil with outstanding ISO cleanliness (max. 17/15/12), high performance level and excellent anti- ageing properties. Provides increased drain interval with outstanding reliability. Meets the requirements of hydraulic systems operating under severe, heavy-duty conditions. Applicable in hydraulic systems of machine- tools, industrial equipment, vehicles, agricultural and off-highway equipment.

PERFORMANCE BENEFITS

PERFORMANCE LEVELS, APPROVALS:

- ISO 11158 HM, ISO-L-HM, DIN 51524-2 (HLP), DIN 51506 VDL, Eaton (Vickers) I-286-S, Eaton (Vickers) M-2950-S, Cincinnati Lamb P-70, ENGEL, AIST (US Steel) 127, AIST (US Steel) 126, AFNOR NF-E-48603 (HM), Parker Denison HF-O, Parker Denison HF-1/HF-2

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3® PREMIUM HYDRAULIC OIL

Product	Hydro HME 46 HP
Kinematic viscosity at 40°C mm ² /s	46.2
Pour point°C	-27
Flash point (Cleveland)°C	225
Density at 15°C g/cm ³	0.875

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.