



TORQU3® SYNTHETIC BIODEGRADABLE HYDRAULIC OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

Biodegradable hydraulic oil based on synthetic ester. Favourably applicable for all stationary and mobile hydraulic systems subject to the risk of leaking hydraulic fluid entering soil, live water courses, ground water or wastewater systems. Readily biodegradable, and provides excellent antiwear and low temperature characteristics. Usable in a wide temperature range: -35 to 70°C.

PERFORMANCE BENEFITS

PERFORMANCE LEVELS, APPROVALS:

- SO 15380 HEES, ISO-L-HEES, VDMA 24568 HEES, SS 155434

Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3
LUBRICANTS

TORQU3® SYNTHETIC BIODEGRADABLE HYDRAULIC OILS

Product	Biohyd 32S	Biohyd 46S
Kinematic viscosity at 40°C mm ² /s	32	48
Pour point°C	-57	-42
Flash point (Cleveland)°C	250	320
Density at 15°C g/cm ³	0.933	0.918

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.