



## TORQU3® SYNTHETIC COMPRESSOR OILS

(Premium Quality, Multigrade, High Performance Engine Oils)

High performance synthetic compressor oils for lubrication of oil-flooded rotary screw and vane compressors as well as reciprocating compressors operating under severe conditions. Due to their excellent wear protection and outstanding resistance to oxidation and thermal degradation extra long service interval can be achieved.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO-L-DAB, ISO-L-DAJ, DIN 51506 VDL, GM LJ-04-3-00, GM LJ-04-3-04, GM LJ-06-3-04, SAE MS1003-2 Type DPJ

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

**TORQU3**  
LUBRICANTS

### TORQU3® SYNTHETIC COMPRESSOR OILS

Product	Compressol RS 46	Compressol RS 68
Kinematic viscosity at 40°C mm <sup>2</sup> /s	45.5	63
Pour point°C	-39	-33
Flash point (Cleveland)°C	225	225
Density at 15°C g/cm <sup>3</sup>	0.846	0.852

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.