



## TORQU3® SYNTHETIC FIRE-RESISTANT HYDRAULIC OIL

(Premium Quality, Multigrade, High Performance Engine Oils)

Fully synthetic, ester based fire-resistant hydraulic fluid (HFDU type), which is free from mineral oil, developed for a wide range of hydraulic systems. Its stable chemical composition provides suitable protection of equipment operating in a wide range of temperatures (-20°C and +120°C ), even under high loads. Due to its carefully selected composition, it has an excellent wear reducing performance, similar to those of gear oils (FZG 12, DIN 51354-Part 2). Recommended for use in high pressure equipment in steel and aluminium industry. Compatible with usual seals and paintings. This product is not toxic, and it has a rapid bio-degradation property.

### PERFORMANCE BENEFITS

#### PERFORMANCE LEVELS, APPROVALS:

- ISO 12922 HFDU, ISO-L-HFDU, 7th Luxemburg Report

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

### TORQU3® SYNTHETIC FIRE-RESISTANT HYDRAULIC OIL

Product	
Kinematic viscosity at 40°C mm <sup>2</sup> /s	48.5
Pour point°C	-36
Flash point (Cleveland)°C	310
Density at 15°C g/cm <sup>3</sup>	0.92

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.