



# TORQU3® 0W20 API SP, ILSAC GF-6A FULLY SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

TORQU3® 0W-20 SP Fully Synthetic redefines excellence in liquid lubricant engineering. Using only selected premium fully synthetic base stocks, top tier additives at peak optimal levels and driven by using technology developed in collaboration with our technology partners in USA. TORQU3® Lubricants has engineered a vastly superior low viscosity engine oil with the latest standards in performance and protection to keep engines running like new day after day. The API SP additive brings the latest enhancements to wear resistance, low speed pre-ignition protection, sludge and deposit protection to keep engines in tip top condition. The SP additive package also conforms to ILSAC GF-6A which brings advanced fuel economy to our oils.

## PERFORMANCE BENEFITS

### FULLY SYNTHETIC FORMULA

- Enhanced thermal stability to withstand higher oxidative stress leading to a longer drain interval. Excellent general lubrication.

### ADVANCED ADDITIVE PACKAGE API SP

- Compared to previous API performance categories the API SP additive package brings performance enhancements in almost all dimensions. These enhancements are seen mainly in fuel economy, fuel economy retention, deposit & sludge reduction, oil oxidation resistance, superior wear resistance and enhanced low speed pre-ignition protection.

### LOW VISCOSITY LOW FRICTION

- Optimal fuel efficiency, excellent throttle response. Easier engine turn over in the cold.

### PREMIUM MULTIGRADE

- Excellent viscosity stability over a wider temperature range enhancing lubrication protection over that temperature range.

### MEETS SPECIFICATIONS & APPROVALS

- API SP
- ILSAC GF-6A
- API CF
- Ford WSS-M2C947-B1

## RECOMMENDATIONS

### API SP

- Suitable for vehicles requiring 5W/20 viscosities and requiring API SP performance grade. Backward compatible, meets API SP and supersedes previous categories.

### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

## TORQU3® 0W-20 SP API SP ILSAC GF-6 FULLY SYNTHETIC

SAE Viscosity Grade		0W-20
Kinematic viscosity at 40°C (cSt)	ASTM D445	46.38
Kinematic viscosity at 100°C (cSt)	ASTM D445	8.78
Density at 15°C	ASTM D4052	0.847
Flash point, °C	ASTM D92	224
Pour point, °C	ASTM D97	-48
Viscosity Index	ASTM D2270	167

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

