



## TORQU3® 10W40 API SP, SEMI SYNTHETIC

(Premium Quality, Multigrade, High Performance Engine Oils)

Developed using the latest in lubricant technology from USA, a blend of premium high end synthetic materials and the highest quality mineral base stocks together with the best top-tier additives available today. TORQU3® Lubricants has developed a vastly superior semi-synthetic medium viscosity lubricant that gives optimal protective and cleaning performance that keeps your engine running like new day after day. The advanced formulation also helps rejuvenate, cleans soot and carbon build up left by inferior oils.

### PERFORMANCE BENEFITS

#### PREMIUM SEMI-SYNTHETIC FORMULATION

- High percentage of fully synthetic base stocks leads to advanced thermal stability to withstand high oxidative stress leading to a longer drain interval. Excellent general lubrication.

#### ADVANCED ADDITIVE PACKAGE API SP

- Designed to protect against low-speed pre-ignition and timing chain wear in gasoline direct injection (GDI) engines. Improved sludge and varnish control coupled with improved high temperature deposit protection for pistons and turbochargers.

#### MEDIUM VISCOSITY

- Less evaporation leading to less top ups while allowing good throttle response & good fuel economy.

#### PREMIUM MULTIGRADE

- Stable viscosity over varying temperatures enhances lubrication protection over a wider temperature range.

#### MEETS SPECIFICATIONS & APPROVALS

- API SP
- API CF

### RECOMMENDATIONS

#### API SP

- Suitable for vehicles requiring SAE 10W-40 viscosities and API SP performance grades. Can be used safely for vehicles requiring SAE 15W-40 viscosities. Backward compatible, meets API SP and supersedes previous categories.

#### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

### TORQU3® 10W40 API SP SEMI SYNTHETIC

SAE Viscosity Grade		10W-40
Kinematic viscosity at 40°C (cSt)	ASTM D445	92
Kinematic viscosity at 100°C (cSt)	ASTM D445	13
Density at 15°C	ASTM D4052	0.867
Flash point, °C	ASTM D92	221
Pour point, °C	ASTM D97	-33
Viscosity Index	ASTM D2270	144

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.

